


2-Line, Uni-directional, Transient Voltage Suppressor



Features


- Stand-off voltage: 70V Max
- Transient protection for each line according to
IEC61000-4-2(ESD): $\pm 30\text{kV}$ (contact)
IEC61000-4-5(surge): 25A (8/20 μs)
- Low leakage current
- Ultra-low capacitance: $C_J = 5\text{ pF typ}$
- Low clamping voltage
- RoHS Compliant

Applications


- ADSL Lines
- Video Line Protection
- I2C Bus Protection
- LAN/WAN equipment
- Portable Electronics
- ISDN S/T Interface

Mechanical Data

- Package: SOT-143
- Case Material: "Green" Molding Compound
- Marking Information: See Below



■Definitions of electrical characteristics





ASR70

■Maximum Ratings

PARAMETER	SYMBOL	LIMITS	UNIT
Peak pulse power ($t_p = 8/20\mu s$), any I/O pin to ground	P_{pk}	250	W
Peak pulse current ($t_p = 8/20\mu s$), any I/O pin to ground	I_{PP}	25	A
ESD according to IEC61000-4-2 air discharge	V_{ESD}	± 30	KV
ESD according to IEC61000-4-2 contact discharge		± 30	
Junction temperature	T_J	-55~125	°C
Storage temperature	T_{STG}	-55~150	°C

■Electrical Characteristics ($T_a=25^\circ C$ Unless otherwise specified)

PARAMETER	Symbol	UNIT	Conditions	Min	Typ	Max
Reverse maximum working voltage	V_{RWM}	V	Any I/O Pin to ground			70
Reverse breakdown voltage	$V_{(BR)}$	V	$I_T = 50\mu A$	85		
Reverse leakage current	I_R	μA	$V_{RWM} = 70V$			5
Clamping voltage	V_{CL}	V	$I_{PP} = 1A$, $t_p = 8/20\mu s$, any I/O pin to ground		.	1.5
		V	$I_{PP} = 25A$, $t_p = 8/20\mu s$ any I/O pin to ground			10
Junction capacitance	CJ	pF	VR = 0V, f = 1MHz, any I/O pin to ground		5	10
			VR = 0V, f = 1MHz, between I/O pins		3	

Notes:

(1). TLP parameter: $Z_0 = 50\Omega$, $t_p = 100ns$, $t_r = 2ns$, averaging window from 60ns to 80ns. RDYN is calculated from 4A to 16A.

(2). Contact discharge mode, according to IEC61000-4-2.

(3). Non-repetitive current pulse, according to IEC61000-4-5

■Ordering Information (Example)

PREFERED P/N	PACKING CODE	UNIT WEIGHT(mg)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
ASR70	F1	Approximate 12	3000	30000	120000	7 reel

■ Characteristics (Typical)

Fig1. 8/20 μ s waveform per IEC61000-4-5




Fig2. Contact discharge current waveform per IEC61000-4-2




Fig3. Clamping voltage vs. Peak pulse current




Fig4. Capacitance vs. Reverse voltage




Fig5. Non-repetitive peak pulse power vs. Pulse time




Fig6. Power derating vs. Ambient temperature









Fig7. TLP Measurement






■ Outline Dimensions



SYM	MILLIMETERS	
	Min	Max
A	0.8	1.22
A1	0	0.15
A2	0.75	1.07
b	0.3	0.51
b1	0.75	0.94
c	0.08	0.2
D	2.8	3.04
E	2.1	2.64
E1	1.2	1.4
e1	1.8	2
L	0.3	0.6

■ Soldering Footprint



SYM	DIMENSIONS	
	MILLIMETERS	INCHES
C	2.20	0.087
E1	1.92	0.076
E2	1.72	0.068
G	0.80	0.031
X1	1.00	0.039
X2	1.20	0.047
Y	1.40	0.055
Z	3.60	0.141

Notes:

This recommended land pattern is for reference purposes only. Please consult your manufacturing group to ensure your PCB design guidelines are met



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.